



**HAYWARD**  
SO YOU CAN BUILD

# Weatherization Systems

Product	RE Code	Units Per Pallet/Cse	Coverage	Order Quantity	Installation Best Practices
<b>Dupont Rolls and Sealants</b>					
3' x 100'	DWRAP3	54 rolls	300 sq. ft./roll		Horizontal overlaps are 2". Vertical overlaps are 6". 12" overlap around inside & outside corners. Use cap fasteners penetrating a minimum of 3/8" into nail bed every 18 inches, may vary depending on wind loads.
9' x 100'	DWRAP9	55 rolls	900 sq. ft./roll		
5' x 100'	STUCCO WRAP	roll each	500 sq. ft./roll		DuPont™ Tyvek® StuccoWrap® WRB has an engineered, grooved surface – that is designed to be installed as a drainage plane behind stucco facades and EIFS systems.
<b>Dupont System and Sealants</b>					
DuPont Butyl Flashing Tape 4"	DTAPE4	roll each	75 linear ft./roll		Use a roller or flashing tool to secure bond.
DuPont Butyl Flashing Tape 6"	DTAPE6	roll each	75 linear ft./roll		
DuPont Butyl Flashing Tape 9"	DTAPE9	roll each	75 linear ft./roll		
6" FlexWrap	DFLEXWRAP	roll each	75 linear ft./roll		DuPont Flex Wrap is a flexible Butyl Flashing Tape used for window pans, complex framing, recessed window bucks and wall to roof interfaces
9" FlexWrap	DFLEXWRAP	roll each	75 linear ft./roll		
2.75" x 15' Flex Wrap EZ	DFLEXEZ	roll each	15 ft./roll		DuPont™ FlexWrap™ EZ is a unique, flexible adhesive tape that creates an airtight and watertight seal around penetrations
<b>Henry Blueskin™ VP100</b>					
48" x 100' Blueskin VP100	BLUESK	36 rolls	400 sq. ft./roll		Apply on clean, dry substrate. 2" overlap on horizontal seams, 3" overlap on vertical seams and 6" around inside & outside corners. Apply pressure to activate adhesive with stiff bristled brush, laminate roller, or Zip roller. Can be applied vertically or horizontally.
<b>Henry Flashing and Sealant Products</b>					
4" x 75' Blueskin Butyl Flash	BTAPE4	12 rolls	75 linear ft./roll		Apply to clean, dry substrate; apply pressure to activate adhesive; can be used for sill pan flashing, leg, and header flashing around windows.
6" x 75' Blueskin Butyl Flash	BTAPE6	8 rolls	75 linear ft./roll		
9" x 75' Blueskin Butyl Flash	BTAPE9	4 rolls	75 linear ft./roll		
Henry 212 All Purpose Sealant	BLUESE	12 tubes	15 linear ft./tube		The only sealant approved to be used to terminate head flashing on VP100. Apply along the top edge where flashing and VP100 meet, continuing 2" down each side of head flashing.
Blueskin Spray Prep	BLUEPR	12 cans			Spray on non-wood substrates to achieve desired adhesion. Wait 45 sec. to apply self-adhered products. Don't use on rubberized asphalt
<b>Stinger® Stapler</b>					
Stinger Stapler	CH 38A	caps sold separately	Each Stapler		The CH38A delivers the holding power of a cap with the speed and ease of a hammertacker. This airless cap system automatically advances the cap and positions it for the staple.
<b>Huber Zip System™</b>					
1/2" x 4' x 8' (Green)	ZIPWALL	70 sheets	32 sq. ft./sheet		Must be applied with code-approved fasteners and fastened through circles or squares that represent either 16" or 24" on center framing. Apply tape over seams using dotted lines for proper coverage and overlap. Make sure to use either 6" or double 3.75" tape on corners and in valleys.
1/2" x 4' x 9' (Green)	ZIPWALL9	62 sheets	36 sq. ft./sheet		
1/2" x 4' x 10' (Green)	ZIPWALL10	56 sheets	40 sq. ft./sheet		
5/8" x 4' x 8' (Red)	ZROOF5SE	55 sheets	32 sq. ft./sheet		





**HAYWARD**<sup>®</sup>  
SO YOU CAN BUILD

# Weatherization Systems

Product	RE Code	Units Per Pallet/Cse	Coverage	Order Quantity	Installation Best Practices
<b>Huber Flashing and Sealant</b>					
3.75" x 90' Seam and Window Tape	ZTAPE	12 rolls	30 linear ft./roll		Apply to clean and dry substrate. Use zip roller to ensure proper pressure is applied for maximum performance and proper adhesion. Use 6" tape for corners and roof valley applications.
6" x 75' Seam and Window Tape	ZTAPE6	4 rolls	90 linear ft./roll		
6" x 20' Stretch Tape	Z5T620	1 per box	75 linear ft./roll		
6" x 75' Stretch Tape	Z5T675	1 per box	20 linear ft./roll		
Liquid Flash	ZSEALANT	20 oz sausage	20 linear ft./roll		<ul style="list-style-type: none"> <li>Creates an air and watertight seal that resists harsh elements</li> <li>Permanently flash and seal building penetrations</li> <li>Bonds to damp or dry surfaces</li> <li>Compatible with most urethane, silicone and acrylic sealants</li> <li>Best for flashing windows</li> </ul>
Zip Roller	ZROLL	Each	30 linear ft./tube		Required to apply pressure to seams and window flashing.
Sausage Gun	Z20 oz gun	Each	1 tube sleeve		Dispensing gun for any foil packed 20 oz Sausage tubes.
<b>Drainage Mats</b>					
Keene Driwall™ Rainscreen 0.25"	DRIWALL™ RAINSCREEN 020-1	1 roll	4' x 65' roll		<p>Driwall™ Rainscreen is a drainage mat for exterior wall systems. The entangled net product eliminates incidental moisture problems in most exterior veneer applications, including stucco, manufactured stone, and plank siding.</p> <p><b>APPLICATIONS</b></p> <ul style="list-style-type: none"> <li>Stucco</li> <li>Stone or brick</li> <li>Manufactured stone</li> <li>Stone and brick masonry</li> <li>Lap siding</li> <li>Siding applications</li> </ul>
Keene DriWall™ Rainscreen 0.40"	DRIWALL™ RAINSCREEN 10MM	1 roll	4' x 25' roll		<p><b>Driwall Rainscreen Products PASS multiple wall assemblies that require NFPA 285.</b></p> <ul style="list-style-type: none"> <li>Drainage of excess moisture and ventilation in one product.</li> <li>Lightweight and easy to handle.</li> <li>Simple installation with mechanical staple hammer</li> <li>Polymer core resistant to most known corrosive chemicals, including solvents.</li> <li>Wide rolls for fewer seams.</li> </ul>
Keene DriWall™ 0.40 Easy-Fur	EASY FUR 10MM	3/rolls/pkg.	4' x 25' roll		<p>Easy-Fur™ is an entangled polymer net furring strip that creates a rainscreen and venting system behind wood and fiber-cement siding. Easy-Fur allows for the fastest installation of any furring strip on the market, because it can be rolled on to the wall and easily cut to length. 1" crown staples can be used for attachment.</p>
<b>Specialty Flashing Products</b>					
Quick Flash Wall Boots	QF P-50	Each	1/2" to 3/4" penetration		<ul style="list-style-type: none"> <li>Stops air leakage</li> <li>Helps to prevent water intrusion</li> <li>Economical — saves time and labor</li> <li>Eliminates the need for sealants</li> <li>Only flashing that is specifically designed for wall penetrations</li> </ul>
Quick Flash Wall Boots	P-100	Each	1" to 1.25" penetration		

